

USA2000J-4-1500DV

4mm Dual View



Monitor	
Power supply	Display
	AC adapter 100~240V, 12V 2.5A, 50-60 Hz Rechargeable Li Battery 3.6V 9800 mAh, approximately operation time: 5hrs, charging time: 4hrs.
Video output	HDMI TYPE D; HDMI 1.4 transmitter with 3D format and CEC support
	USB USB TYPE C, supporting USB full- speed and high-speed data transmission
	Wi-Fi IEEE802.11 B/G/N
Operating temperature	
With battery power 0°C ~ 45°C With AC adapter power 0°C ~ 35°C	
Drop resistance	
1m	
Relative humidity	
Max 95% non-condensing	
Storage temperature	
IP57	
Insert tubes interchangeability	
6.0mm HD series; 3.9mm series	

USA2000 Probe	
	4mm Dual View
Probe head diameter	3.9mm
Probe head length	21.6mm
Direction of View	Front + Side View
Illumination	Front + Side LEDs
Field of View (FOV)	120°
Depth of Field (DOF)	5mm~100mm
Still image resolution (.jpg)	(Dual) 1600x1600
Video resolution (.mov)	(Dual) 1600*1600
Articulation angle	Full ways≥120°
Probe length	1.5m
Operating temperature	In air: -10~100°C, In water:10~30°C
Probe head material	Stainless steel
Probe material	Tungsten braided